

**APPLETS LIFE CYCLE:**

Applet life cycle means the various states through which applet passes during its object creation and removal. Each state is a method. There are total five states (methods), which are shown as :

|   |  |
|---|--|
|  |  |
|---|--|

These methods are called automatically.

[init\(\)](#), [start\(\)](#), [stop\(\)](#), [destroy\(\)](#) methods are defined in [java.applet.Applet](#) class. [paint\(\)](#) method is defined in [java.awt.Component](#) class, an indirect superclass of Applet.

[init\(\)](#): The applet starts here. In this method, the applet object is created by the browser, but objects are in inactive states.

This method is suitable to,

Initialize variables, instantiate objects, and colors in GUI etc.

[start\(\)](#): To make the applet object active, the [init\(\)](#) method calls [start\(\)](#) method, which makes applet active for processor time.

[paint\(\)](#): This method belongs to [java.awt.Graphics](#), which includes many methods of drawing necessary to draw on the applet window. In this method programmer can write his code of what he expects from applet like animation etc. This is similar to runnable state of thread.

**stop():** In this method the applet becomes temporarily inactive. An applet can come any number of times into this method in its life cycle and can go back to the active state (paint()).It is similar to the blocked state of the thread.

**destroy():** This method is called to end of the life cycle of an applet. It is similar to the dead state of the thread.

**WHEN ABOVE METHODS ARE CALLED:**

**init():** Browser called this method at the time of starting the execution. This is called only once in the life cycle.

**start():** This method is called by the init() method, a number of times in the life cycle , to make the applet active.

**paint():** This method is called by the start() method, number of times in the execution.

**stop():** This method is called to inactivate the applet. This method is called number of times in the execution.

**destroy():** This method is called to close the applet, called only once in the life cycle.

## Related Posts:

1. Can Java have same name variable
2. Types of variables in Java programming
3. JAVA and its Support Systems
4. JAVA environment
5. JAVA program structure
6. Tokens
7. Java statements
8. Java virtual machine
9. C++ Versus JAVA
10. Constants and Variables in Java
11. Data types JAVA
12. Defining a class
13. Constructor in JAVA
14. Array in Java
15. Applet
16. Applets Vs Applications
17. Writing applets
18. Creating an Executable Applet
19. Graphics in Applet
20. Applet image display
21. Applet digital clock
22. Applet mouse event handling
23. JDBC
24. Execute an SQL Statement
25. Process the result
26. CLOSE THE DATABASE CONNECTION

27. File handling
28. Define a class to declare an integer array of size n and accept the elements into the array.
29. Define a class to declare an array of size 20 of the double datatype, accept the elements into the array and perform the following: Calculate and print the sum of all the elements.
30. Java program for String, to uppercase, to equal, length of string
31. Write a Java program for Buble sort.
32. Write a Java program String to uppercase and count words startig with 'A'
33. How to set path in Java
34. Understanding public static void main (String args[] ){ } in Java
35. Difference between static and non static methods in Java