

In Java, statements are individual instructions or commands that perform a specific action. Each statement typically ends with a semicolon (;) to mark its completion.

Here are some common types of statements in Java:

## 1. Variable Declaration and Assignment:

```
int age; // Variable declaration
age = 25; // Variable assignment
```

This statement declares an integer variable named age and assigns the value 25 to it.

## 2. Expression Statements:

```
int result = 10 + 5; // Expression statement
System.out.println("The result is: " + result); // Method invocation statement
```

Expression statements perform operations or function calls. The first statement adds 10 and 5, and assigns the result to the variable result. The second statement calls the println method to display a message along with the value of result.

## 3. Control Flow Statements:

- [REDACTED]

```
int number = 7;
if (number % 2 == 0) {
    System.out.println("The number is even.");
} else {
    System.out.println("The number is odd.");
}
```

This statement checks if number is divisible by 2. If the condition is true, it prints “The number is even.”; otherwise, it prints “The number is odd.”

- 

```
for (int i = 0; i < 5; i++) {
    System.out.println("Iteration: " + i);
}

int count = 0;
while (count < 3) {
    System.out.println("Count: " + count);
    count++;
}

int value = 0;
do {
    System.out.println("Value: " + value);
    value++;
} while (value < 3);
```

These statements demonstrate different types of loops. The for loop executes a block of code repeatedly for a specified number of iterations. The while loop continues execution until a

certain condition is met. The do-while loop first executes the code block and then checks the condition for further iterations.

## 4. Jump Statements:

- 

```
for (int i = 0; i < 10; i++) {
    if (i == 5) {
        break; // Exit the loop when i equals 5
    }
    System.out.println("Value: " + i);
}

- `continue` statement:
```java
for (int i = 0; i < 10; i++) {
    if (i == 5) {
        continue; // Skip the current iteration when i equals 5
    }
    System.out.println("Value: " + i);
}
```

The break statement is used to exit a loop prematurely, while the continue statement skips the current iteration and moves to the next iteration of a loop.

## Related Posts:

1. Can Java have same name variable
2. Types of variables in Java programming
3. JAVA and its Support Systems

4. JAVA environment
5. JAVA program structure
6. Tokens
7. Java virtual machine
8. C++ Versus JAVA
9. Constants and Variables in Java
10. Data types JAVA
11. Defining a class
12. Constructor in JAVA
13. Array in Java
14. Applet
15. Applets Vs Applications
16. Writing applets
17. Applets life cycle
18. Creating an Executable Applet
19. Graphics in Applet
20. Applet image display
21. Applet digital clock
22. Applet mouse event handling
23. JDBC
24. Execute an SQL Statement
25. Process the result
26. CLOSE THE DATABASE CONNECTION
27. File handling
28. Define a class to declare an integer array of size n and accept the elements into the array.
29. Define a class to declare an array of size 20 of the double datatype, accept the

elements into the array and perform the following: Calculate and print the sum of all the elements.

30. Java program for String, to uppercase, to equal, length of string
31. Write a Java program for Buble sort.
32. Write a Java program String to uppercase and count words startig with 'A'
33. How to set path in Java
34. Understanding public static void main (String args[] ){ } in Java
35. Difference between static and non static methods in Java