## **NETWORK VIRTUALIZATION**

#### **Network virtualization:**

- 1. Network virtualization is a method of combining the available resource in a network by splitting up the available bandwidth into channels each of which is independent from the other and each of which can be designed to a particular server or device in real time.
- 2. Each channel is independently secured. Every subscriber has shared access to all the resources on the network from a single computer.
- 3. Network virtualization is intended to improve productivity, efficiency and job satisfaction of the administrator by performing many of these tasks automatically thereby disguising the true complexity of the network.
- 4. Files, images, programs and folder can be centrally managed from a single physical site. Storage media such as hard drives and tape drives can be easily added or reassigned. Storage space can be shared or reallocated among the server.
- 5. Virtual LAN is an example of network virtualization that provides easy flexible and less expensive way to manage networks.

### Virtual LAN:

1. VLANs logically segment switched networks based on the functions, project teams, or applications of the organization regardless of the physical location or connections to the

#### network.

- 2. All workstations and servers used by a particular workgroup share the same VLAN, regardless of the physical connection or location.
- 3. A workstation in a VLAN group is restricted to communicating with file servers in the same VLAN group.
- 4. VLANs function by logically segmenting the network into different broadcast domains so that packets are only switched between ports that are designated for the same VLAN.
- 5. Routers in VLAN topologies provide broadcast filtering, security, and traffic flow management.
- 6. VLANs address scalability, security, and network management.
- 7. Switches may not bridge any traffic between VLANs, as this would violate the integrity of the VLAN broadcast domain.
- 8. Traffic should only be routed between VLANs.

# Additional VLAN components include:

- 1. High performance switches that logically segment connected end stations.
- 2. Transport protocol that carry VLAN traffic across LAN and ATM backbone.

- 3. Layer 3 routing solutions that existed VLAN communication between workgroup.
- 4. System compatibility and interoperability the previously installed LAN system.
- 5. Network management solution that offers centralized control , configuration and traffic management function.

## **Related Posts:**

- 1. Information Life Cycle Management (ILM)
- 2. Storage infrastructure
- 3. Integrated VS Modular Array
- 4. Data proliferation
- 5. Data categorization
- 6. Component architecture of intelligent disk subsystem
- 7. Intelligent disk subsystems overview
- 8. Mapping n operations
- 9. Storage system architecture
- 10. RAID
- 11. Hot spare
- 12. SAN security
- 13. JBOD
- 14. Elements of DAS, NAS, CAS, SAS
- 15. Limitations of DAS
- 16. Cloud vocabulary
- 17. NAS security
- 18. Management of DAS, NAS, CAS, SAN
- 19. FC Connectivity

- 20. Memory virtualization
- 21. Data center concepts & requirements
- 22. Server information storage and management
- 23. ISM Architectural Framework